

Serial No.: 09/587,058

REMARKS

As indicated by the Examiner in Paper No. 16 attached is claim 8 properly underlined.

It is believed that no fees or charges are required at this time in connection with the present application; however, if any fees or charges are required at this time, they may be charged to our Patent and Trademark Office Deposit Account No. 03-2412.

Respectfully submitted,
COHEN, PONTANI, LIEBERMAN & PAVANE

By



Thomas C. Pontani
Reg. No. 29,763
551 Fifth Avenue, Suite 1210
New York, New York 10176
(212) 687-2770

Dated: August 8, 2002

Serial No.: 09/587,058

AMENDMENTS TO THE CLAIMS SHOWING CHANGES

In the Claims:

8. (Twice Amended) A single disc friction clutch for a motor vehicle, said friction clutch comprising:

a clutch housing;

a clutch disc;

said single clutch disc being configured to be mounted on a transmission input shaft having a longitudinal axis;

21 said single clutch disc being configured to be axially movable along the longitudinal axis of a transmission input shaft;

a pressure plate;

at least one friction lining mounted on said clutch disc;

said at least one friction lining being configured to be disposed between said pressure plate and a flywheel;

said pressure plate being configured and disposed to engage and disengage said clutch disc with a flywheel;

said pressure plate being configured and disposed to be axially movable along the longitudinal axis of a transmission input shaft;

a membrane spring;

said membrane spring being disposed between said clutch housing and said pressure plate;

said membrane spring being configured and disposed to bias said pressure plate;

Serial No.: 09/587,058

said pressure plate comprising a first portion and a second portion;

said first portion of said pressure plate being disposed to contact said clutch disc;

said second portion of said pressure plate being disposed away from said clutch disc;

a thermal insulating member being configured to minimize heat conduction from said pressure plate to said membrane spring;

said pressure plate having a protrusion extending axially in the direction of said membrane spring;

said insulating member being disposed at said protrusion between said membrane spring and said first portion of said pressure plate;

said second portion of said pressure plate forming part of said protrusion and being disposed between said insulating member and said membrane spring to contact said membrane spring;

said insulating member being rigid and comprising a metal and being a single, one-piece element extending circumferentially above said pressure plate;

said metal of said insulating member being configured to minimize heat conduction from said first portion of said pressure plate to said membrane spring to minimize distortion of

said membrane spring from thermal conduction of heat from said pressure plate to said membrane spring.

cont